


DI825

Compact Product Suite hardware selector



The DI825 is an 8 channel 125 V d.c. digital input module for the S800 I/O. The input range is 71 - 150 V and the input current is 3.0 mA at 125 V. The inputs are individually isolated.

Every input channel consists of current limiting components, EMC protection components, input state indication LED, optical isolation barrier. Channel 1 can be used as voltage supervision input for channels 2 - 4, and channel 8 can be used as voltage supervision input for channels 5 - 7.

If the voltage supervision is used and the voltage connected to channel 1 or 8 disappears, the channel error will be set for the channels and the Warning LED turns on. The error signal can be read from the ModuleBus.

Features and benefits

- 8 channels for 125 V d.c. inputs
- Individually isolated channels
- Input status indicators
- Sequence of event (SOE) functionality
- Signal filtering

General info	
Type	Digital Input
Signal specification	125 V d.c.
Article number	3BSE036373R1
Number of channels	8
Signal type	Current sinking
HART	No
SOE	Yes
Redundancy	No
High integrity	No
Intrinsic safety	No
Mechanics	S800

Detailed data	
Input voltage range, "0"	0..20 V
Input voltage range, "1"	71..156 V
Input impedance	41.5 kΩ
Isolation	Individually isolated channels
Filter times (digital, selectable)	0..100 ms
Current limiting	Sensor power can be current limited by the MTU
Maximum field cable length	600 meters (656 yards)
Event recording accuracy	-0.25 ms...1.0 ms
Event recording resolution	0.4 ms
Rated insulation voltage	250 V
Dielectric test voltage	2300 V a.c. Ch - Ground, 1350 V a.c. Ch - Ch
Power dissipation	Max. 4.9 W
Current consumption +5 V Modulebus	Max. 90 mA
Current consumption +24V Modulebus	0
Current consumption +24V external	0

Diagnostics	
Front LED's	F(ault), R(un), W(arning), Channel 1-8 Status
Supervision	Process voltage. Channel 1 and 8 can be used per group
Status indication of supervision	Module Error, Module Warning, Channel error

Environment and certification	
CE mark	Yes
Electrical safety	IEC 61131-2, UL 508
Hazardous Location	-
Marine certification	-
Protection rating	IP20 according to IEC60529
Corrosive atmosphere ISA-S71.04	G3
Climatic operating conditions	0 to +55 °C (Storage -40 to +70 °C), RH=5 to 95 % no condensation, IEC/EN 61131-2
Pollution degree	Degree 2, IEC 60664-1
Mechanical operating conditions	IEC/EN 61131-2
EMC	EN 61000-6-4 and EN 61000-6-2
Overvoltage categories	IEC/EN 60664-1, EN 50178
Equipment class	Class I according to IEC 61140; (earth protected)
Max ambient temperature	55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)
RoHS compliance	EN 50581:2012
WEEE compliance	DIRECTIVE/2012/19/EU

Compability	
Use with MTU	TU811, TU813, TU831, TU839, TU851
Keying code	AB

Intrinsic Safety parameters

Dimensions	
Width	45 mm (1.77")
Depth	102 mm (4.01"), 111 mm (4.37") including connector
Height	119 mm (4.7")
Weight	0.14 kg (0.31 lbs.)

Related products



TU839



TU831V1



TU811V1



TU813



TU851

www.abb.com/800xA
www.abb.com/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2019 ABB All rights reserved