

DI828

Compact Product Suite hardware selector



The DI828 is an 16 channel 120 V a.c/d.c. digital input module for the S800 I/O. The module has 16 digital inputs. The AC input voltage range is 77 - 130 V and the input current is 8.5 mA at 120V AC. The DC input voltage range is 75 - 130 V and the input current is 2.4 mA at 120V DC. The inputs are individually isolated. Every input channel consists of current limiting components, EMC protection components, input state indication LED, optical isolation barrier and an analog filter. Channel 1 can be used as voltage supervision input for channels 2 - 8. Channel 16 can be used as voltage supervision input for channels 9 - 15. If the voltage supervision is used and the voltage connected to channel 1 or 16 disappears, the channel error will be set for the channels and the Warning LED turns on. The error signal can be read from the ModuleBus.

Features and benefits

- 16 channels for 120 V AC/DC inputs
- Individually isolated channels
- Input status indicators
- Signal filtering

General info	
Type	Digital Input
Signal specification	120 V a.c. / d.c.
Article number	3BSE069054R1
Number of channels	16
Signal type	Current sinking
HART	No
SOE	No
Redundancy	No
High integrity	No
Intrinsic safety	No
Mechanics	S800

Detailed data	
Input voltage range, "0"	0..30 V a.c., 0..20 V d.c.
Input voltage range, "1"	77..130 V a.c., 75..130 V d.c.
Input impedance	14.2 k Ω (a.c.) / 50 k Ω (d.c.)
Isolation	Individually isolated channels
Filter times (digital, selectable)	2,5 \pm 0.5, 5 \pm 1, 10 \pm 2, 20 \pm 4 ms
Input frequency range	47..63 Hz
Analog filter On/Off delay	5 / 10 ms
Maximum field cable length	200 meters (656 yards) 100 pF/m for a.c., 600 meters (656 yards) for d.c.
Rated insulation voltage	250 V
Dielectric test voltage	2000 V a.c.
Power dissipation	Typ. 3.5 W
Current consumption +5 V Modulebus	Typ. 45 mA, Max 60 mA
Current consumption +24 V Modulebus	0

Diagnostics	
Front LED's	F(ault), R(un), W(arning), Channel 1-16 ("0" or "1")
Supervision	Process voltage, Channel 1 and 16 can be used per group
Status indication of supervision	Module Error, Module Warning, Channel error

Environment and certification	
CE mark	Yes
Electrical safety	IEC 61131-2
Hazardous Location	C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2
Marine certification	ABS, BV, DNV-GL, LR, RS
Protection rating	IP20 according to IEC60529
Corrosive atmosphere ISA-S71.04	G3
Climatic operating conditions	0 to +55 °C (Storage -40 to +70 °C), RH=5 to 95 % no condensation, IEC/EN 61131-2
Pollution degree	Degree 2, IEC 60664-1
Mechanical operating conditions	IEC/EN 61131-2
EMC	EN 61000-6-4 and EN 61000-6-2
Overvoltage categories	IEC/EN 60664-1, EN 50178
Equipment class	Class I according to IEC 61140; (earth protected)
Max ambient temperature	55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)
RoHS compliance	EN 50581:2012

Compability	
Use with MTU	EB
Keying code	TU851

Intrinsic Safety parameters

Dimensions	
Width	45 mm (1.77")
Depth	102 mm (4.01"), 111 mm (4.37") including connector
Height	119 mm (4.7")
Weight	0.15 kg (0.33 lbs.)

Related products



TU851



www.abb.com/800xA
www.abb.com/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2018 ABB All rights reserved