

DATA SHEET

TB826 (Single Mode) Compact Product Suite hardware selector



S800 I/O is a comprehensive, distributed and modular process I/O system that communicates with parent controllers and PLCs over industry-standard field buses. TB826 is a Long range Optical Media Converter for the ModuleBus. It is used to convert between plastic/opto fiber of HCS fiber with versatile link connectors and single mode field fiber with SC connector.

The TB826 is built in S800L mechanics and DIN rail mounted. TB826 allows distribution of the optical ModuleBus up to 5000 m per cluster in star configurations.

Features and benefits

- Converts between plastic or HCS opto fiber and glass optical fiber
- DIN rail mounted
- Allows distribution of optical ModuleBus up to 5000 m per cluster in star configurations
- S800L mechanics

General info		
Article number	3BSE061637R1	
Communication protocol	Modulebus	
Master or slave	Slave	
Line redundancy	No	
Module redundancy	No	
Hot Swap	No	
Used together with HI Controller	Yes	

Detailed data		
24 V consumption typ.	96 mA	

Environment and certification		
CE- marking	Yes	
Electrical Safety	EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201	
Hazardous location	C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2	
Marine certificates	-	
Temperature, Operating	0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C	
Temperature, Storage	-40 to +70 °C (-40 to +158 °F)	
Pollution degree	Degree 2, IEC 60664-1	
Corrosion protection	ISA-571.04: G3	
Relative humidity	5 to 95 %, non-condensing	
Max ambient temperature	55 °C (131 °F), for vertical mounting 40 °C (104 °F)	
Protection class	IP20 according to EN60529, IEC 529	
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)	
WEEE compliance	DIRECTIVE/2012/19/EU	

Dimensions	
Width	85.6 mm (3.37 in.)
Height	136 mm (5.35 in.) including latch
Depth	58.5 mm (2.30 in.)
Weight	0.21 kg (0.46 lbs)



solutions.abb/compactproductsuite solutions.abb/controlsystems

_

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document. We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved