

SD822Z

Compact Product Suite hardware selector



SD822Z, SD83x, SS822Z, SS823 and SS832 is a range of space saving power supplies intended for the AC 800M, AC 800M-eA, S800 I/O and S800-eA I/O product lines. Output current can be selected in the range of 3-20 A and the input range is wide. Relevant voters for redundant configurations are available.

The range also supports power supply configurations of the AC 800M and S800 I/O based IEC 61508-SIL2 and SIL3 rated solutions. A Mains Breaker Kit for DIN Rail is also available for our power supplies and voters.

Features and benefits

- Simple DIN-rail mounting
- Class I Equipment, (when connected to Protective Earth, (PE))
- Over-voltage Category III for connection to primary main TN network
- Protective separation of secondary circuit from primary circuit
- Accepted for SELV and PELV applications
- The output of the units is protected against over current (current limit) and over voltage (OVP)
- SD822Z is also G3 compliant

General info

Article number	3BSC610054R1
Type	Power supply
Rated output current	5 A
Rated output power	120 W
Rated output voltage	d.c. 24 V
Rated input power	280 VA 135 W
Mains/input voltage, nominal	115/230 V a.c. 225-250 V d.c.
Applications	SELV and PELV

Detailed data	
Mains voltage variation allowed	85 - 110%
Mains/input voltage, max. (a.c.= 45-65 Hz)	138/275 V a.c. 375 V d.c.
Primary peak inrush current at power on	Type 15 A
Load sharing	Two in parallell
Heat dissipation	13.3 W
Output voltage regulation at max. current	+ - 2%
Ripple (peak to peak)	< 50 mV
Secondary voltage holdup time at mains blackout	> 20 ms
Maximum output current (min)	10 A
Maximum ambient temperature	60 °C
Primary: Recommended external fuse (1)	10 A
Secondary: Short circuit	< 10 A
Secondary: Over-Voltage protection	29 V

Environmental and certification	
CE mark	Yes
Electrical safety	IEC 61131-2, UL 508, EN 50178
Marine certification	ABS, BV, DNV-GL, LR, RS
Protection rating	IP20 according to IEC 60529
Corrosive atmosphere ISA-S71.04	G3
Pollution degree	Degree 2, IEC 60664-1
Mechanical operating conditions	IEC 61131-2
EMC	EN 61000-6-4 and EN 61000-6-2
Overvoltage Categories	Over-voltage Category III (IEC/EN 60664-1)
Equipment class	Class 1 according to EN 50718; 3.56
RoHS compliance	EN 50581:2012
WEEE compliance	DIRECTIVE/2012/19/EU

Dimensions	
Width	65 mm (2.56 in.)
Depth	110 mm (4.3 in.)
Height	125 mm (4.9 in.)
Weight (lbs.)	620 g (1.4 lbs)
Mounting spacing W mm	15 mm (0.59 in.)
Mounting spacing H mm	25 mm (1 in.)

www.abb.com/800xA
www.abb.com/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2018 ABB All rights reserved