

# TU830V1

## Compact Product Suite hardware selector



The TU830V1 MTU can have up to 16 I/O channels and two process voltage connections. Each channel has two I/O connections and one ZP connection. The MTU is a passive unit used for connection of the field wiring to the I/O modules. It also contains a part of the ModuleBus.

The process voltage can be connected to two individually isolated groups. Each group has a 6.3 A fuse. The maximum rated voltage is 50 V and maximum rated current is 2 A per channel. The MTU distributes the ModuleBus to the I/O module end to the next MTU. It also generates the correct address to the I/O module by shifting the outgoing position signals to the next MTU.

### Features and benefits

- Complete installation of I/O modules using 3-wire connections, fuses and field power distribution.
- Up to 16 channels of field signals and process power connections.
- Connections to ModuleBus and I/O modules.
- Mechanical keying prevents insertion of the wrong I/O module.
- Latching device to DIN rail for grounding.
- DIN rail mounting.

| General info         |  |
|----------------------|--|
| Article number       | 3BSE013234R1   |
| Type                 | Extended   |
| Connection           | Terminal block   |
| Channels             | 16   |
| Voltage              | 50 V   |
| Mounting             | Both directions  |
| Mounting detail      | 55 °C (131 °F)   |
| Use with I/O         | AI810, AI815, AI820, AI830, AI830A, AI835, AI835A, AI843, AI845, AO810, AO810V2, AO815, AO820, AO845, AO845A, DI810, DI811, DI814, DI830, DI831, DI840, DI880, DI885, DO810, DO814, DO815, DO840, DO880, DP820 and DP840 |
| Process connections  | 56   |
| Single/redundant I/O | Single   |

| <b>Detailed data</b>               |   |
|------------------------------------|---|
| Maximum current per I/O channel    | 2 A   |
| Maximum current process connection | 5 A   |
| Acceptable wire sizes              | Solid: 0.2 - 4 mm <sup>2</sup><br>Stranded: 0.2 - 2.5 mm <sup>2</sup> , 24 - 12 AWG<br>Recommended torque: 0.5 - 0.6 Nm<br>Stripping length: 7 mm |
| Dielectric test voltage            | 500 V a.c.  |

| <b>Environment and certification</b> |   |
|--------------------------------------|---|
| CE mark                              | Yes   |
| Electrical safety                    | IEC 61131-2, UL 508   |
| Hazardous Location                   | C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2                                      |
| Marine certification                 | ABS, BV, DNV-GL, LR, RS, CCS  |
| Protection rating                    | IP20 according to IEC 60529   |
| Corrosive atmosphere ISA-S71.04      | G3  |
| Climatic operating conditions        | 0 to +55 °C (Storage -40 to +70 °C), RH=5 to 95 % no condensation, IEC/EN 61131-2 |
| Pollution degree                     | Degree 2, IEC 60664-1   |
| Mechanical operating conditions      | IEC/EN 61131-2  |
| EMC                                  | EN 61000-6-4, EN 61000-6-2  |
| Overvoltage categories               | IEC/EN 60664-1, EN 50178  |
| Equipment class                      | Class I according to IEC 61140; (earth protected)                                 |
| RoHS compliance                      | EN 50581:2012   |
| WEEE compliance                      | DIRECTIVE/2012/19/EU  |

| <b>Dimensions</b> |  |
|-------------------|--|
| Width             | 126 mm (5 in.) including connector, 120.5 mm (4.74 in.) edge to edge installed |
| Depth             | 64 mm (2.52 in.) including terminals   |
| Height            | 110 mm (4.3 in.)   |
| Weight            | 0.28 kg (0.6 lbs)  |

---

[www.abb.com/800xA](http://www.abb.com/800xA)  
[www.abb.com/controlsystems](http://www.abb.com/controlsystems)

---

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2018 ABB All rights reserved